

CLAIMS

- [001] A coffee machine comprising a drawer for supplying coffee pads into a brewing chamber of the coffee machine (110), characterised in that the drawer (122, 210, 342) is positioned on the coffee machine (110) in a detachable manner for the withdrawal thereof.
- [002] The coffee machine according to claim 1, characterised in that the drawer (122, 210, 342) has continuations (130, 218, 344) which project substantially in the direction of insertion and which engage in guides of the housing of the coffee machine (110) for mounting the drawer (122, 210, 342) in an open position.
- [003] The coffee machine according to claim 2, characterised in that the ends of the continuations (130, 218, 344) are at least slightly bevelled with respect to the direction of insertion for centring insertion of the drawer (122, 210, 342).
- [004] The coffee machine according to any one of claims 1 to 3, characterised in that in a closed position, the drawer (122, 210, 342) abuts at least partly positively against the housing.
- [005] The coffee machine according to any one of the preceding claims, characterised in that the drawer (122, 210, 342) can be inserted substantially horizontally into a niche (120) of the coffee machine and the drawer (122, 210, 342) has at least one opening in its base which, in the closed position of the drawer (122, 310, 342), is at least partially surrounded by at least one substantially vertically displaceable retaining device so that the coffee pad retainer (220) can be raised by the retaining device and the brewing chamber (330) is closed by raising the coffee pad retainer (220).
- [006] The coffee machine according to any one of the preceding claims, characterised in that in addition to a central opening, further openings are provided in the bottom of the drawer (122, 210, 342).

- 11 -

[007] The coffee machine according to any one of the preceding claims, characterised in that the coffee pad retainer (220, 320) is mounted telescopically on the drawer (122, 210, 342).